



Safety Data Sheet

RF 1142 Part A

Section 1. Identification

Product Identifier	RF 1142 Part A		
Synonyms	Epoxy resin		
Manufacturer Stock Numbers	31441		
Recommended use	Epoxy Resin		
Uses advised against	Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, strong mineral and organic base, especially primary and secondary aliphatic amines.		
Manufacturer Contact Address	Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA		
	Phone	Emergency Phone	Fax
	(310) 204-6159	(800) 424-9300 CHEMTREC	(310) 202-7247
	Email	Website	
	sales@evroberts.com	http://www.evroberts.com	

Section 2. Hazards Identification

Classification	EYE DAMAGE/IRRITATION - Category 2B SKIN CORROSION/IRRITATION - Category 3
Signal Word	Warning
Pictogram	
Hazard Statements	Causes mild skin irritation

Precautionary Statements	Moderately irritating to eyes
Response	If skin irritation occurs: Get medical advice/attention.
Prevention	N/A
Storage	Store in a cool, dry area. Keep at a temperature below 77 Degrees F
Disposal	Refer to manufacturer/Supplier for information on recovery/recycling

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

EMERGENCY OVERVIEW

Health Hazards	Moderately irritating to skin. May cause sensitization by continuous contact with skin or vapors (especially if heated). Moderately irritating to eyes.
Physical Hazards	Reacts with strong oxidizing agents, amines, acids (Lewis or mineral). Will exotherm when reacting. This reaction accelerates at higher temperatures
Appearance	Clear, light yellow or Colored (if pigmented with one of the available colors) Resinous liquid
Odor	Slightly Sweet Odor
MSDS	Read the entire MSDS for a more thorough evaluation of the hazards.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
111031-82-4	Chromium, aqua chloro hydroxy methacrylate complexes	<1 %
17557-23-2	Oxirane, 2,2'-[(2,2-dimethyl-1,3-propanediyl)bis(oxyethylene)]bis-	<15 %
65997-17-3	Glass, oxide, chemicals	<50 %
28064-14-4	Phenol, polymer with formaldehyde, glycidyl ether	<65 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Remove patient from exposure, keep warm and at rest. Obtain medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, qualified personnel should administer oxygen. Apply artificial respiration if breathing has ceased or shows signs of failing.
Skin	Wash with soap and water.
Eye Contact	Immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists repeat flushing and obtain medical attention IMMEDIATELY.
Ingestion	Do NOT Induce Vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, if conscience, wash out their mouth with water then give 1 or 2 glasses of water to drink. Refer person to medical personnel for immediate attention.
Note to Physician	In general, emesis induction is unnecessary in high viscosity, low volatility products, e.g. Neat Epoxy Resins. However, symptomatic and supportive therapy may be needed following severe exposure. In such cases, medical follow-up should be maintained for at least 48 hours.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media

Containers may burst under intense heat due to reaction with water, a hazardous build-up of pressure could result if contaminated containers are re-sealed.

Extinguishing media:

Carbon dioxide, dry chemical or appropriate foam. If water is used, very large quantities are required. Reaction between water and hot isocyanate may be vigorous. Contain runoff water with temporary barriers.

Protective Equipment:

Use self-contained breathing apparatus and full protective clothing (Bunker Gear).

Flash Point:

No Data

Flammable Limits (Lower):

Not Available

Flammable Limits (Upper):

Not Available

Auto Ignition Temperature:

Not Available

Decomposition Temperature:

~600 Degrees F (315 Degrees C)

Rate of Burning:

Not Available

Explosive Power:

None

Sensitivity to Mechanical Impact:

None

Sensitivity to Static Discharge:

None

Decomposition Products:

Carbon monoxide, Aldehydes, Acids and other organic substances may be formed during the combustion or thermal or oxidative decomposition. Reaction with some curing agents may produce considerable heat (exotherm), Run-a-way cure reaction may char and decompose the resin system, generating unidentified fumes and vapors, which may be toxic.

Unsuitable Extinguishing Media

N/A

Section 6. Accidental Release Measures

Major Spills	For Major Spills, call CHEMTREC at 1-800-424-9300
Spills, Leaks or Releases	Clean up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection. Evacuate the area. Prevent further leakage, spillage or entry into drains. Contain and absorb large spillages onto an inert, non-flammable absorbent carrier (such as earth or sand), Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spillage area clean with liquid decontaminant. Remove and dispose of residues. Notify applicable government authorities if release is reportable. Small spills: Take up with an absorbent material and dispose of properly.

Section 7. Handling and Storage

Special Precautions	<p>Emptied containers can contain hazardous product residues. Handle in accordance with the hazard potential of curing agent(s) used. Avoid contact with eyes, avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Launder contaminated clothing before reuse. Contaminated leather articles, including shoes, can not be decontaminated and should be destroyed.</p> <p>Warning: may cause skin and eye irritation. May cause skin sensitization. Minimize bodily contact. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Heating this material above 300°F in the presence of air may cause slow oxidative decomposition. Above 500°F, polymerization may occur. Some curing agents, eg. Aliphatic amines can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from these thermal and chemical decompositions vary widely in composition and toxicity. DO NOT BREATHE FUMES. Use a NIOSH-approved respirator.</p>
Handling	Avoid personal contact with the product or reaction mixture. Use only with adequate ventilation to ensure that the defined occupational exposure limit is not exceeded. The efficiency of the ventilation must be monitored regularly because of the possibility of blockage. Avoid breathing aerosols, mists and vapors. When the product is sprayed or heated, an approved MSHA/NIOSH positive-pressure, supplied-air respirator may be required.
Storage Requirements	Keep containers properly sealed and when stored indoors, in a well ventilated area. Keep contents away from open flames and high temperatures.
Storage Temperature	Ideal storage temperature is 16-38°C (60-100°F)
Shelf Life	12 Months @ 77°F (25°C)

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Chromium, aqua chloro hydroxy methacrylate complexes	N/A	N/A	N/A
	Oxirane, 2,2'-[(2,2-dimethyl-1,3-propanediyl)bis (oxymethylene)]bis-	N/A	none	N/A
	Glass, oxide, chemicals	N/A	N/A	N/A
	Phenol, polymer with formaldehyde, glycidyl ether	N/A	N/A	N/A
<p>Personal Protective Equipment</p> <p>Preventive Measures</p>	<p>Goggles, Gloves, Face Shield, CHEMICAL GOGGLES, PROTECTIVE CLOTHING</p> <p>Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.</p>			
<p>Engineering Controls</p>	<p>Use local exhaust ventilation to maintain airborne concentrations below the TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it. Follow guidelines in the ACGIH publication "Industrial Ventilation".</p>			
<p>Personal Protective Equipment</p> <p>Eye Protection</p>	<p>Chemical safety goggles. If there is a potential for splashing, use a full-face shield.</p>			
<p>Skin Protection</p>	<p>The following protective materials are recommended. Gloves - neoprene, nitrile-butadiene rubber, butyl rubber. Thin disposable gloves should be avoided for repeated or long term use. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.</p>			
<p>Respiratory Protection</p> <p>Protective Clothing</p>	<p>Not ordinarily required</p> <p>Avoid contact with eyes. Wear safety goggles as appropriate. Wear chemical resistant clothing as required to minimize contact</p>			

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Clear to light yellow
Odor	Sweet Odor
Odor Threshold	N/A
Solubility	Negligible
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	N/A
Specific Gravity	1
Density lbs/Gal	8.34
Pounds per Cubic Foot	N/A
Flash Point	N/A
FP Method	N/A
Ph	N/A
Melting Point	<77°F (25°C)
Boiling Point	N/A
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	N/A
Vapor Density	N/A

Section 10. Stability and Reactivity

Hazardous Decomposition Products	Carbon monoxide, aldehydes, acids and other organic substances may be formed during the combustion or thermal or oxidative decomposition. Reaction with some curing agents may produce considerable heat (exothermic). Run-A-Way cure reactions may char and decompose the resin system, generating unidentified fumes and vapors which may be toxic.
Chemical Stability	Stable at room temperature
Conditions to Avoid	Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, and strong mineral and organic bases, especially primary and secondary aliphatic amines.

Section 11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

Inhalation	Not expected to be relevant route of exposure. However, high vapor or aerosol mist concentrations may be irritating to the nose, throat and upper respiratory tract.
Skin Contact	Moderate irritant. Repeated and/or prolonged contact may cause skin sensitization.
Eye Contact	The aerosol, vapor or liquid will irritate human eyes following contact.
Ingestion	Ingestion may cause irritation of the gastrointestinal tract. This product is considered to have a low order of acute oral toxicity.
Chronic Effects	Repeated contact can cause skin sensitization. Preexisting skin, eye and respiratory may be aggravated by exposure to this product.
Carcinogenicity	Epichlorohydrin, CAS 106-89-8, an impurity in this product, (<50 PPM), has been reported to produce cancer in laboratory animals and to produce mutagenic changes in bacteria and cultured human cells. It has been established by the International Agency for Research on Cancer (IARC) as a probable human carcinogen (IARC Group 2A) based on the following conclusions: Human evidence - inadequate; animal evidence - sufficient. It has been classified as an anticipated human carcinogen by the National Toxicology Program (NTP)
Mutagenicity	There is no substantial evidence of mutagenic potential.
Reproductive Effects	No adverse reproductive effects are anticipated.
Teratogenicity and Fetotoxicity	No information is available and no adverse teratogenic embryotoxic effects are anticipated.

Section 12. Ecological Information

Environmental Release Information	Keep out of surface waters, sewers and waterways entering or leading to surface waters. Notify authorities if any exposure to the general public or environment occurs or is likely to occur.
-----------------------------------	---

Section 13. Disposal

Disclaimer Part 1	The generation of waste should be avoided or minimized wherever possible.
Disclaimer Part 2	Disposal should be in accordance with local, state, provincial and national regulations. This material is not a hazardous waste under RCRA 40 CFR 261. Small quantities should be treated with a liquid decontaminate. The treated waste is not a hazardous material under RCRA 40 CFR 261. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.
Disclaimer Part 3	Empty containers should be decontaminated and either passed to an approved drum recycler or destroyed.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A
DOT	Not hazardous by DOT regulations

Section 15. Regulatory Information

Regulatory

This product is listed on the EPA/TSCA inventory of chemical substances. Protection of stratospheric ozone (pursuant to Section 611 of the Clean Air Act Amendment of 1990); Per 40 CFR Part 82, this product does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances. In accordance with SARA Title III, Section 313.

Section 16. Other Information

Revision Date

7/28/2015

HMIS Rating (Not Regulated) The HMIS Rating for this product is:
Health: 2 Flammability: 1 Reactivity: 0

0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

Disclaimer

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of E.V. Roberts' product safety program. It is not intended to constitute performance information concerning the product. No warranty, expressed or implied, or merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. E.V. Roberts does not undertake to furnish advice on such matters.



Safety Data Sheet

RF 1142 Part B

Section 1. Identification

Product Identifier	RF 1142 Part B		
Synonyms	Epoxy curing agent		
Manufacturer Stock Numbers	31441		
Recommended use	Epoxy Curing Agent		
Uses advised against	Do not store in reactive metal containers. Avoid heat, flames, sparks and other sources of ignition. Store away from nitrites.		
Manufacturer Contact Address	Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA		
	Phone	Emergency Phone	Fax
	(310) 204-6159	(800) 424-9300 CHEMTREC	(310) 202-7247
	Email	Website	
	sales@evroberts.com	http://www.evroberts.com	

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - DERMAL - Category 4 ACUTE TOXICITY - INHALATION - Category 5 ACUTE TOXICITY - ORAL - Category 4 EYE DAMAGE/IRRITATION - Category 1
Signal Word	Danger
Pictogram	The pictogram section contains two red diamond-shaped hazard symbols. The first symbol shows a hand being poured on by a test tube, representing skin irritation. The second symbol is a large black exclamation mark, representing a general hazard.

Hazard Statements	Causes serious eye damage Harmful if swallowed Harmful in contact with skin May be harmful if inhaled
Precautionary Statements	
Response	Call a poison center/doctor/ ... /if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Call a POISON CENTER or doctor/... if you feel unwell If on skin: Wash with plenty of water/ ... If swallowed: Call a poison center/doctor/ ... / if you feel unwell. Immediately call a poison center/doctor/ ... Rinse mouth. Specific treatment (see ... on this label) Take off immediately all contaminated clothing and wash it before reuse.
Prevention	Do not eat, drink or smoke when using this product. Wash ...thoroughly after handling. Wear eye protection/face protection. Wear protective Butyl Gloves, Face Shield, Eye Bath and Safety Shower.
Storage	N/A
Disposal	Refer to manufacturer/Supplier for information on recovery/recycling
Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	
Emergency Overview	Warning: Toxic in contact with skin. Corrosive. Moderate respiratory irritant. Severe skin irritant. Severe eye irritant. May cause sensitization by skin contact.
Potential Health Effects	
Inhalation	Can cause severe eye, skin and respiratory tract burns. May cause nose, throat, and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.
Eye contact	Causes eye burns. May cause blindness. Severe eye irritation.
Skin contact	Causes skin burns. Toxic in contact with skin.
Chronic Health Hazard	This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Prolonged contact may result in chemical burns and permanent damage. Repeated or prolonged contact causes sensitization, asthma and eczemas.
Exposure Guidelines	
Target Organs	Skin, Eyes, Respiratory System
Symptoms	Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat.
Aggravated Medical Condition	Eye disease, Skin disorders and Allergies. Adverse skin effects (such as rash, irritation or corrosion) Adverse eye effects (such as conjunctivitis or corneal damage). Adverse respiratory effects (such as cough, tightness of chest or shortness of breath) and Asthma.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
68909-20-6	Silamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	<0.5 %
112-24-3	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-	<99 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

General	Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
Eye	Rinse immediately with plenty of water also under the eyelids for at least 20 minutes. Remove contact lenses.
Skin	Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Wash off immediately with plenty of water for at least 20 minutes. Cover wound with sterile dressing. Take off contaminated clothing and shoes immediately. NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.
Ingestion	Do not induce vomiting without medical advice. If a person vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Turn victim's head to the side.
Inhalation	If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	<p>Extinguishing media: Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical Dry sand Limestone powder.</p> <p>Specific Hazards: May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces obnoxious and toxic fumes.</p> <p>Special Protective Equipment for Fire-Fighters Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary.</p> <p>Further Information: Do not allow run-off from fire fighting to enter drains or water courses.</p>
Unsuitable Extinguishing Media	N/A

Section 6. Accidental Release Measures

Personal precautions	Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.
Environmental Precautions	Construct a dike to prevent spreading
Methods for cleaning up	Approach suspected leak areas with caution. Contact Air Products Emergency Response Center for advice. Place in appropriate chemical waste container.
Additional Advice	If possible, stop flow of product

Section 7. Handling and Storage

Handling	Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer-causing nitrosamines could be formed. Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. Use personal protective equipment. When using, do not eat, drink or smoke.
Storage	Store in steel containers preferably located outdoors, above ground, and surrounded by dikes to contain spills or leaks. Do not store near acids. Keep containers tightly closed in a dry, cool and well-ventilated place.
Technical measures/Precautions	Do not store in reactive metal containers

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	N/A	N/A	N/A
	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-	N/A	N/A	N/A
Personal Protective Equipment Engineering Measures	Goggles, Gloves, Face Shield, Respirator, PROTECTIVE CLOTHING, VENTILATION, EYE WASH AND SAFETY SHOWER Provide readily accessible eye wash stations and safety showers. Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.			
Personal Protective Equipment Respiratory Protection Hand protection	Wear appropriate respirator when ventilation is inadequate. Neoprene gloves. Butyl-rubber. Nitrile rubber. Impervious gloves. The breakthrough time of the selected glove(s) must be greater than the intended use period.			
Eye protection	Full face shield with goggles underneath. Chemical resistant goggles must be worn.			
Skin and Body Protection	Slicker Suit. Impervious clothing. Full rubber suit (rain gear). Rubber or plastic boots. Long sleeve shirt and trousers without cuffs.			
Environmental exposure controls	Construct a dike to prevent spreading.			
Special Instructions for protection and hygiene	Discard contaminated leather articles. Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Provide readily accessible eye wash stations and safety showers. Wash at the end of each workshift and before eating, smoking or using the toilet.			
Exposure Limits	Triethylenetetramine: Time Weighted Average (TWA):WEEL; 1ppm; 6 mg/m3.			

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Amber
Odor	Fishy
Odor Threshold	N/A
Solubility	Completely soluble
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	20 mPa.s at 77°F (25°C)
Specific Gravity	1
Density lbs/Gal	0.98
Pounds per Cubic Foot	N/A
Flash Point	>115.56°C
FP Method	N/A
Ph	Alkaline
Melting Point	N/A
Boiling Point	531°F (277°C)
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	<0.01 mmHg at 21°C
Vapor Density	5.61

Note If used with a pigment, the color is orange.

Section 10. Stability and Reactivity

No Data Available

Section 11. Toxicological Information

Acute Health Hazard

Ingestion	LD50 : > 2,500 mg/kg Species : Rat.
Inhalation	No data is available on the product itself.
Skin	LD50 : > 805 mg/kg Species : Rabbit.
Eye Irritation	Severe eye irritation.
Acute Dermal Irritation/corrosion	Severe skin irritation.
Sensitization	May cause sensitization by skin contact. Sensitization has occurred in laboratory animals after repeated exposures.

Section 12. Ecological Information

Ecotoxicity Effects

Aquatic Toxicity	No data is available on the product itself.
Toxicity to other organisms	No data available.
Persistence and degradability	Mobility: No data available Bioaccumulation: No data is available on the product itself.

Section 13. Disposal

Waste from residues / unused products	Contact supplier if guidance is required.
Contaminated packaging	Dispose of container and unused contents in accordance with federal, state, and local requirements.

Section 14. Transport Information

UN Number	2259
UN Proper Shipping Name	Triethylenetetramine
DOT Classification	8
Packing Group	II
Further Information	Note: If regulated as a hazardous material (Dangerous Good) in transportation, please refer to shipping papers or contact Air Products for complete shipping description information.

Section 15. Regulatory Information

OSHA Hazard Communication Standard Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Classes:
Corrosive, Sensitizer

USA (TSCA) Included on inventory
EU (EINECS) Included on EINECS inventory or polymer
substance, monomers included on EINECS
inventory or no longer polymer
Canadian (DSL) Included on Inventory.
Australia (AICS) Included on Inventory.
Japan (ENCS) Included on Inventory.
South Korea (ECL) Included on Inventory.
China (SEPA) Included on Inventory.
Philippines (PICCS) Included on Inventory.

EPA SARA TITLE III Section 312 (40CFR370) Hazard Classification:
Acute Health Hazard, Chronic Health Hazard

EPA SARA TITLE III Section 313 (40CFR372)
Component(s) above de minimus level: None

CALIFORNIA PROPOSITION 65

WARNING: This product does not contain any chemicals that are known to the
State of California to cause cancer, birth defects or other reproductive harm.

WHMIS Hazard Classification:
Toxic material causing other toxic effects

Section 16. Other Information

Revision Date

7/29/2015

HMIS Rating (Not Regulated)

The HMIS Rating for this product is:
Health: 3 Flammability: 1 Reactivity: 0

0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

For Information Purposes Only - No Longer Regulated

Disclaimer

The information contained herein is believed to be accurate. It is provided
independently of any sale of the product for purpose of hazard communication as
part of E.V. Roberts' product safety program. It is not intended to constitute
performance information concerning the product. No warranty, expressed or
implied, or merchantability or fitness for a particular purpose is made with
respect to the product or the information contained herein.

To determine applicability or effects of any law or regulation with respect to the
product, user should consult his legal advisor or the appropriate government
agency. E.V. Roberts does not undertake to furnish advice on such matters.