



Safety Data Sheet

RF 134

Section 1. Identification

Product Identifier	RF 134		
Synonyms	Epoxy Resin Color Pigment Paste		
Manufacturer Stock Numbers	10386		
Recommended use	Yellow Pigment Epoxy Paste		
Uses advised against	Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, strong mineral and organic base, especially primary and secondary aliphatic amines.		
Manufacturer Contact			
Address	Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA		
	Phone	Emergency Phone	Fax
	(310) 204-6159	(800) 424-9300 CHEMTREC	(310) 202-7247
	Email	Website	
	sales@evroberts.com	http://www.evroberts.com	

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - INHALATION - Category 5 EYE DAMAGE/IRRITATION - Category 2B SKIN CORROSION/IRRITATION - Category 3
Signal Word	Warning
Pictogram	

Hazard Statements Causes mild skin irritation
May be harmful if inhaled
Moderately irritating to eyes

Precautionary Statements

Response IF INHALED: Call a POISON CENTER or doctor/... if you feel unwell
If skin irritation occurs: Get medical advice/attention.

Prevention Wear protective gloves/eye protection/face protection

Storage Store in a well-ventilated place. Keep container tightly closed.

Disposal Refer to manufacturer/Supplier for information on recovery/recycling

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

EMERGENCY OVERVIEW

Health Hazards:
Moderately irritating to skin. May cause sensitization by continuous contact with skin or vapors (especially if heated). Moderately irritating to eyes.

Physical Hazards:
Reacts with strong oxidizing agents, amines, acids (Lewis of mineral). Will exothermic when reacting. This reaction accelerates at higher temperatures.

Appearance:
Resinous liquid, Honey - like consistency

Odor:
Slightly sweet odor.

Read the entire MSDS for a more thorough evaluation of the hazards.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
	Zinc Compounds	10-15 %
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane	70-75 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

General	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Remove patient from exposure, keep warm and at rest. Obtain medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, qualified personnel should administer oxygen. Apply artificial respiration if breathing has ceased or shows signs of failing.
Skin Contact	Remove contaminated clothing. Wash affected areas thoroughly with soap and water. If irritation, redness, or a burning sensation develops and persists, obtain medical advice. Contaminated clothing should be thoroughly cleaned before reuse. Contaminated leather articles can not be decontaminated and should be destroyed.
Eye Contact	Immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists repeat flushing and obtain medical attention IMMEDIATELY.
Ingestion	Do NOT Induce Vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, if conscience, wash out their mouth with water then give 1 or 2 glasses of water to drink. Refer person to medical personnel for immediate attention.
Note to Physician	In general, emesis induction is unnecessary in high viscosity, low volatility products, e.g. Neat Epoxy Resins. However, symptomatic and supportive therapy may be needed following severe exposure. In such cases, medical follow-up should be maintained for at least 48 hours.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media

Containers may burst under intense heat due to reaction with water, a hazardous build-up of pressure could result if contaminated containers are re-sealed.

Extinguishing media:

Carbon dioxide, dry chemical or appropriate foam. If water is used, very large quantities are required. Reaction between water and hot isocyanate may be vigorous. Contain runoff water with temporary barriers.

Protective Equipment:

Use self-contained breathing apparatus and full protective clothing (Bunker Gear).

Flash Point:

485°F (252°C) (setaflash)

Flammable Limits (Lower):

Not Available

Flammable Limits (Upper):

Not Available

Auto Ignition Temperature:

Not Available

Decomposition Temperature:

~600 Degrees F (315 Degrees C)

Rate of Burning:

Not Available

Explosive Power:

None

Sensitivity to Mechanical Impact:

None

Sensitivity to Static Discharge:

None

Decomposition Products:

Carbon monoxide, Aldehydes, Acids and other organic substances may be formed during the combustion or thermal or oxidative decomposition. Reaction with some curing agents may produce considerable heat (exotherm), Run-a-way cure reaction may char and decompose the resin system, generating unidentified fumes and vapors, which may be toxic.

Unsuitable Extinguishing Media

N/A

Section 6. Accidental Release Measures

Major Spills	For Major Spills, call CHEMTREC at 1-800-424-9300
Spills, Leaks or Releases	Clean up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection. Evacuate the area. Prevent further leakage, spillage or entry into drains. Contain and absorb large spillages onto an inert, non-flammable absorbent carrier (such as earth or sand), Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spillage area clean with liquid decontaminant. Remove and dispose of residues. Notify applicable government authorities if release is reportable. Small spills: Take up with an absorbent material and dispose of properly.

Section 7. Handling and Storage

Special Precautions	<p>Emptied containers can contain hazardous product residues. Handle in accordance with the hazard potential of curing agent(s) used. Avoid contact with eyes, avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Launder contaminated clothing before reuse. Contaminated leather articles, including shoes, can not be decontaminated and should be destroyed.</p> <p>Warning: may cause skin and eye irritation. May cause skin sensitization. Minimize bodily contact. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Heating this material above 300°F in the presence of air may cause slow oxidative decomposition. Above 500°F, polymerization may occur. Some curing agents, eg. Aliphatic amines can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from these thermal and chemical decompositions vary widely in composition and toxicity. DO NOT BREATHE FUMES. Use a NIOSH-approved respirator.</p>
Handling	Avoid personal contact with the product or reaction mixture. Use only with adequate ventilation to ensure that the defined occupational exposure limit is not exceeded. The efficiency of the ventilation must be monitored regularly because of the possibility of blockage. Avoid breathing aerosols, mists and vapors. When the product is sprayed or heated, an approved MSHA/NIOSH positive-pressure, supplied-air respirator may be required.
Storage Requirements	Keep containers properly sealed and when stored indoors, in a well ventilated area. Keep contents away from open flames and high temperatures.
Storage Temperature	Ideal storage temperature is 16-38°C (60-100°F)
Shelf Life	12 Months @ 77°F (25°C)

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Zinc Compounds	N/A	N/A	N/A
	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane	N/A	none	N/A
<p>Personal Protective Equipment</p> <p>Preventive Measures</p>	<p>Goggles, Gloves, Apron, Face Shield, CHEMICAL GOGGLES, PROTECTIVE CLOTHING</p> <p>Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.</p>			
<p>Engineering Controls</p>	<p>Use local exhaust ventilation to maintain airborne concentrations below the TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it. Follow guidelines in the ACGIH publication "Industrial Ventilation".</p>			
<p>Personal Protective Equipment</p> <p>Eye Protection</p>	<p>Chemical safety goggles. If there is a potential for splashing, use a full-face shield.</p>			
<p>Skin Protection</p>	<p>The following protective materials are recommended. Gloves - neoprene, nitrile-butadiene rubber, butyl rubber. Thin disposable gloves should be avoided for repeated or long term use. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.</p>			
<p>Respiratory Protection</p> <p>Protective Clothing</p>	<p>Not ordinarily required</p> <p>Avoid contact with eyes. Wear safety goggles as appropriate. Wear chemical resistant clothing as required to minimize contact</p>			

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Yellow Pigmented Paste
Odor	Sweet Odor
Odor Threshold	N/A
Solubility	Negligible
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	N/A
Specific Gravity	1.353
Density lbs/Gal	9.9
Pounds per Cubic Foot	N/A
Flash Point	485°F (252° C)
FP Method	setaflash
Ph	N/A
Melting Point	Below 77°F (25°C)
Boiling Point	N/A
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	~600°F (315° C)
Auto-ignition Temperature	N/A
Vapor Pressure	< 1
Vapor Density	N/A

Section 10. Stability and Reactivity

Hazardous Decomposition Products	Carbon monoxide, aldehydes, acids and other organic substances may be formed during the combustion or thermal or oxidative decomposition. Reaction with some curing agents may produce considerable heat (exothermic). Run-A-Way cure reactions may char and decompose the resin system, generating unidentified fumes and vapors which may be toxic.
Chemical Stability	Stable at room temperature
Conditions to Avoid	Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, and strong mineral and organic bases, especially primary and secondary aliphatic amines.

Section 11. Toxicological Information

Acute Toxicity Data	Bis A epichlorohydrin: Acute Oral LD50: 11.4g/kg (rat) Acute Dermal LD50: <20g/kg (rabbit) Acute Inhalation LD50: No Deaths, SAT. Air, 8 hr
POTENTIAL HEALTH EFFECTS:	
Inhalation	Not expected to be relevant route of exposure. However, high vapor or aerosol mist concentrations may be irritating to the nose, throat and upper respiratory tract.
Skin Contact	Moderate irritant. Repeated and/or prolonged contact may cause skin sensitization.
Eye Contact	The aerosol, vapor or liquid will irritate human eyes following contact.
Ingestion	Ingestion may cause irritation of the gastrointestinal tract. This product is considered to have a low order of acute oral toxicity.
Chronic Effects	Repeated contact can cause skin sensitization. Preexisting skin, eye and respiratory may be aggravated by exposure to this product.
Carcinogenicity	Epichlorohydrin, CAS 106-89-8, an impurity in this product, (<50 PPM), has been reported to produce cancer in laboratory animals and to produce mutagenic changes in bacteria and cultured human cells. It has been established by the International Agency for Research on Cancer (IARC) as a probable human carcinogen (IARC Group 2A) based on the following conclusions: Human evidence - inadequate; animal evidence - sufficient. It has been classified as an anticipated human carcinogen by the National Toxicology Program (NTP)
Mutagenicity	There is no substantial evidence of mutagenic potential.
Reproductive Effects	No adverse reproductive effects are anticipated.
Teratogenicity and Fetotoxicity	No information is available and no adverse teratogenic embryotoxic effects are anticipated.

Section 12. Ecological Information

Environmental Release Information	Keep out of surface waters, sewers and waterways entering or leading to surface waters. Notify authorities if any exposure to the general public or environment occurs or is likely to occur.
-----------------------------------	---

Section 13. Disposal

Disclaimer Part 1	The generation of waste should be avoided or minimized wherever possible.
Disclaimer Part 2	Disposal should be in accordance with local, state, provincial and national regulations. This material is not a hazardous waste under RCRA 40 CFR 261. Small quantities should be treated with a liquid decontaminate. The treated waste is not a hazardous material under RCRA 40 CFR 261. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.
Disclaimer Part 3	Empty containers should be decontaminated and either passed to an approved drum recycler or destroyed.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	N/A
DOT Classification	N/A
Packing Group	N/A
DOT	Not hazardous by DOT regulations

Section 15. Regulatory Information

Regulatory	This product is listed on the EPA/TSCA inventory of chemical substances. In accordance with SARA Title III, Section 313, of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372, this product contains the following substance: ZINC COMPOUNDS, 10-15 % by weight
------------	---

Section 16. Other Information

Revision Date	5/22/2015
HMIS Rating (Not Regulated)	The HMIS Rating for this product is: Health: 2 Flammability: 1 Reactivity: 0 0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

Disclaimer	<p>NOTICE: While the descriptions, designs data, and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. It is provided independently of any sale of the product for purpose of hazard communication as part of E.V. Roberts' product safety program. Many factors may affect processing or application/use. We recommend you make tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties or merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sales. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by E.V. Roberts hereunder are given gratis and E.V. Roberts assumes no obligation or liability for the description, designs, data and information given or results obtained, all such being given and accepted at your risk.</p>
------------	---

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. E.V. Roberts does not undertake to furnish advice on such matters.