



Safety Data Sheet

RF 2239 Part A

Section 1. Identification

Product Identifier	RF 2239 Part A		
Synonyms	Formulated epoxy resin		
Manufacturer Stock Numbers	12176		
Recommended use	Formulated Epoxy Resin		
Uses advised against	Avoid strong acids, strong bases, strong oxidizers, amines, mercaptans		
Manufacturer Contact Address	Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA		
	Phone	Emergency Phone	Fax
	(310) 204-6159	(800) 424-9300 CHEMTREC	(310) 202-7247
	Email	Website	
	sales@evroberts.com	http://www.evroberts.com	

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - DERMAL - Category 5 ACUTE TOXICITY - INHALATION - Category 5 ACUTE TOXICITY - ORAL - Category 4 EYE DAMAGE/IRRITATION - Category 2B
Signal Word	Warning
Pictogram	A black exclamation mark is centered within a red diamond-shaped border.
Hazard Statements	Causes eye irritation

Causes gastrointestinal irritation
 Harmful if swallowed
 May be harmful if inhaled
 May be harmful in contact with skin

Precautionary Statements

Response Call a poison center/doctor/ ... /if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF INHALED: Call a POISON CENTER or doctor/... if you feel unwell
 If swallowed: Call a poison center/doctor/ ... / if you feel unwell.
 Rinse mouth.

Prevention Do not eat, drink or smoke when using this product.
 Wash ...thoroughly after handling.

Storage N/A

Disposal Refer to manufacturer/Supplier for information on recovery/recycling

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

EMERGENCY OVERVIEW

WARNING!
 EYE IRRITANT.
 SKIN IRRITANT.
 SKIN SENSITIZER.
 Colorless Liquid No Odor.

Eye Irritating, but will not permanently injure eye tissue.

Skin Irritating to skin. May cause sensitization by skin contact. Heated material can cause thermal burns.

Inhalation Unlikely to be hazardous by inhalation because of the low vapor pressure of the material at ambient temperature. Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

Ingestion Ingestion may cause irritation of the gastrointestinal tract.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
7631-86-9	Fumed Silica	<10 %
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane	>50 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists repeat flushing and obtain medical attention IMMEDIATELY.
Skin	Remove grossly contaminated clothing and shoes. Wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse and discard shoes.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do not attempt to give anything by mouth to an unconscious person. If individual is conscious, give water to dilute stomach contents. Get prompt medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	<p>Auto Ignition Temperature: Not Available</p> <p>Flash Point: >200°F</p> <p>Extinguishing media: Use alcohol-resistant foam, water spray or FOG, CO2, dry chemical. Do not use direct water stream on burning liquid.</p> <p>Special Fire Fighting Procedures: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.</p> <p>Fire and Explosion Hazards: Combustible at high temperatures. Combustion will evolve toxic and irritant vapors. Prolonged exposure to elevated temperatures may cause uncontrolled exothermic reactions resulting in decomposition and charring of the material.</p> <p>Hazardous Combustion Products: Thermal decomposition products are hazardous and/or toxic. Carbon dioxide, carbon monoxide Aldehydes</p> <p>Flammable Limits (Lower): Not Available</p> <p>Flammable Limits (Upper): Not Available</p>
Unsuitable Extinguishing Media	N/A

Section 6. Accidental Release Measures

Spill and Leak Procedures	Evacuate immediate area and dike area to contain spill. Extinguish open flames and ignition sources in the immediate area. Use cautious judgment when cleaning up large spills. Clean up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection, gloves and splash goggles. Absorb as much spilled material as possible with rags, sand, vermiculite or other absorbent material. Scrape absorbed material into designated waste containers. Wash area thoroughly with detergent and rinse, taking care to prevent runoff into drains or other waterways. All spilled material, absorbed waste and wash water must be disposed of in accordance with all federal, state and local regulations.
Environmental Precautions	For safety and environmental precaution, please review the entire Safety Data Sheet for necessary information.

Section 7. Handling and Storage

Storage Temperature	Ideal storage temperature is 25°C
Shelf Life	12 Months @ 77°F (25°C)
Storage	Keep container closed when not in use.
Sensitivity to Static Electricity	No
Sensitivity to Mechanical Impact	No
Special Sensitivity	Avoid excessive heat
Other Precautions	This material should not be spilled, dumped or flushed down water drains, sewers or watercourses.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Fumed Silica	N/A	10 mg/m ³ , TLV-TWA, Inhalation	N/A
	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane	N/A	none	N/A
Personal Protective Equipment Ventilation Eye protection Hand protection	Goggles, Gloves, PROTECTIVE CLOTHING, SAFETY GLASSES Local exhaust ventilation recommended if generating vapor, dust or mist. If exhaust ventilation is not available or inadequate, use NIOSH approved respirator as appropriate. Safety glasses or goggles required. Neoprene gloves. Butyl-rubber. Nitrile rubber. Impervious gloves. The breakthrough time of the selected glove(s) must be greater than the intended use period.			
Skin and Body Protection	Standard issue work clothes. Safety boots - chemical resistant without lace holes.			
Hygienic Practices - Clothing	Launder contaminated clothes before wearing. Do not smoke or eat where this material is being used. Wash hands before smoking, eating or going to the bathroom			
Hygienic Practices	Wash all exposed areas well with soap and water. Remove and launder all contaminated clothes and shoes before wearing.			

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	none
Odor Threshold	N/A
Solubility	insoluble
Partition coefficient Water/n-octanol	N/A
VOC%	N/A
Viscosity	N/A
Specific Gravity	1.2
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>200°F
FP Method	N/A
Ph	N/A
Melting Point	N/A
Boiling Point	>400°F
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Negligible
Vapor Density	>1.0

Section 10. Stability and Reactivity

Chemical Stability	Stable under recommended storage temperatures and pressures.
Materials to Avoid	Strong acids, strong bases, strong oxidizers, amines, mercaptans
Conditions to Avoid	HEAT
Hazardous Decomposition Products	Carbon Monoxide, Carbon Dioxide, aldehydes.
Reactivity	May polymerize with amine compounds.

Section 11. Toxicological Information

Route of Entry	Eye Contact, Skin Contact, Inhalation, Ingestion
Carcinogen	Carcinogen IARC NTP OSHA Substance Component (group) Specific Regulation
	COMPONENT There is no evidence that this product poses a carcinogenic risk under normal conditions of handling and use.
Chronic (Long Term) Effects of Exposure	Effects of Chronic Exposure The toxicological properties of this product have not been fully evaluated. Use of good industrial hygiene practices is required. Avoid direct contact with skin or eyes. Do not ingest or inhale.
Target Organs	Skin
Skin Sensitization	Sensitizer. May cause allergic reaction.
PRODUCT TOXICOLOGY:	
Product Information	This data sheet is based on a consideration of the properties of the constituents. Slightly irritant to skin and eyes. When heated, the vapor given off can cause irritation of the eyes, nose and respiratory tract. COMPONENT: Epoxy resin ORAL TOXICITY: Oral LD50; Rat > 5000 mg/kg Note: Unlikely to be hazardous if swallowed. COMPONENT: Epoxy resin DERMAL TOXICITY: Dermal LD50; Rat > 6000 mg/kg Note: Repeated or prolonged skin contact may result in moderate irritation. Repeated and/or prolonged contact may cause skin sensitization. COMPONENT: Epoxy resin INHALATION TOXICITY: Note: Unlikely to be hazardous if inhaled because of the low vapor pressure of the material at ambient temperature. COMPONENT: Epoxy resin Note: May cause eye irritation.

Section 12. Ecological Information

Potential Effect on Environment	May cause harm to aquatic organisms. Do not allow to enter drains, sewers or watercourses.
Mobility	Insoluble
Persistence and Degradability	Not readily biodegradable
Potential to Bioaccumulate	The product has low potential for bioaccumulation.
Aquatic Toxicity	None Established

Section 13. Disposal

WASTE DISPOSAL METHOD: Dispose of in accord with local, state and federal regulations

Empty Container Precautions Follow all MSDS/label precautions even after container is emptied because they may retain product residues.

Section 14. Transport Information

UN Number N/A

UN Proper Shipping Name N/A

DOT Classification N/A

Packing Group N/A

DOT NOT REGULATED Not regulated by DOT regulations if 119 gallon capacity or less

All Regulatory Classification This product is not regulated by CFR, TDG, IMO, IMDG or IATA

Section 15. Regulatory Information

Regulatory Information

TSCA All components are on the TSCA inventory.
Canadian Domestic Substance List (DSL) Is on DSL.
China (IECSC) On the IECSC Inventory.
Japan (ENCS) On the ENCS Inventory.
Australia (AICS) On the AICS Inventory.
Korea (KECI) On the KECI Inventory.
Philippines (PICCS) On the PICCS Inventory.
EINECS All components of this product are listed in EINECS or ELINCS.

SARA - Section 313 (Superfund Amendments and Reauthorization Act of 1986 - 40CFR372) Contains no substances at or above the reporting threshold under Section 313.

CALIFORNIA PROPOSITION 65
WARNING: This product contains the following chemicals that are known to the State of California to cause cancer, birth defects or other reproductive harm. Unless a concentration is specified in Section 2 of the SDS, the below chemicals are present in trace amounts:

COMPONENT: Phenyl glycidyl ether
CAS NUMBER: 122-60-1

COMPONENT: Epichlorohydrin
CAS NUMBER: 106-89-8

Section 16. Other Information

Revision Date

8/21/2015

HMIS Rating (Not Regulated) The HMIS Rating for this product is:
Health: 2 Flammability: 1 Reactivity: 0

0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

Disclaimer

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of E.V. Roberts' product safety program. It is not intended to constitute performance information concerning the product. No warranty, expressed or implied, or merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. E.V. Roberts does not undertake to furnish advice on such matters.



Safety Data Sheet

RF 2239 Part B

Section 1. Identification

Product Identifier	RF 2239 Part B		
Synonyms	Amine catalyst		
Manufacturer Stock Numbers	12176		
Recommended use	Catalyst		
Uses advised against	Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids, strong mineral and organic base, especially primary and secondary aliphatic amines.		
Manufacturer Contact Address	Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA		
	Phone	Emergency Phone	Fax
	(310) 204-6159	(800) 424-9300 CHEMTREC	(310) 202-7247
	Email	Website	
	sales@evroberts.com	http://www.evroberts.com	

Section 2. Hazards Identification

Classification	ACUTE TOXICITY - DERMAL - Category 3 ACUTE TOXICITY - ORAL - Category 3 EYE DAMAGE/IRRITATION - Category 2A SKIN CORROSION/IRRITATION - Category 2
Signal Word	Danger

Pictogram



Hazard Statements

Causes serious eye irritation
Moderately irritating to skin
Toxic if swallowed
Toxic in contact with skin

Precautionary Statements

Response

Call a poison center/doctor/ ... /if you feel unwell.
If eye irritation persists: Get medical advice/attention.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If on skin: Wash with plenty of water/ ...
If swallowed: Immediately call a poison center/doctor/...
Rinse mouth.
Specific treatment (see ... on this label)
Take off immediately all contaminated clothing and wash it before reuse.

Prevention

Do not eat, drink or smoke when using this product.
Wash ...thoroughly after handling.
Wear eye protection/face protection.
Wear protective Butyl Gloves, Face Shield, Eye Bath and Safety Shower.

Storage

Store locked up.

Disposal

Dispose of contents/container to ...

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified
Emergency Overview

WARNING:
SEVERE EYE IRRITANT.
TOXIC IF SWALLOWED.
TOXIC IN CONTACT WITH SKIN.
HARMFUL IF SWALLOWED.
SKIN IRRITANT.
RESPIRATORY SENSITIZER.
SKIN SENSITIZER.
Colorless Liquid Amine odor

Eye contact

Severe/very severe eye irritant.

Skin

Irritating to the skin. Can be absorbed through skin causing systemic toxic effect.
Repeated and/or prolonged contact may cause skin sensitization.

Inhalation

Vapor or aerosol, if generated, can cause irritation of the eyes, nose and respiratory tract. Possible respiratory sensitizer.

Ingestion

Moderately toxic. Irritant and may cause nausea and vomiting.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
68082-29-1	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethy	>50 %
112-24-3	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-	5-10 %
61788-32-7	Terphenyl, hydrogenated	5-10 %

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact	Immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists repeat flushing and obtain medical attention IMMEDIATELY.
Skin Contact	Flush exposed areas thoroughly with soap and water until all chemical is removed. Remove contaminated clothing and launder before reuse. Obtain immediate medical attention.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do not attempt to give anything by mouth to an unconscious person. If individual is conscious, give water to dilute stomach contents. Get prompt medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	<p>Auto Ignition Temperature: Not Available</p> <p>>170° C (Pensky-Martens Closed Tester)</p> <p>CO2, dry chemical, Foam</p> <p>Special Fire Fighting Procedures: Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.</p> <p>Containers may burst under intense heat.</p> <p>Hazardous Combustion Products: Thermal decomposition products are hazardous and/or toxic. Carbon dioxide, carbon monoxide. Nitrogen oxides. Ammonia</p> <p>Flammable Limits (Lower): Not Available</p> <p>Flammable Limits (Upper): Not Available</p>
Unsuitable Extinguishing Media	N/A

Section 6. Accidental Release Measures

Spill and Leak Procedures	Evacuate immediate area and dike area to contain spill. Extinguish open flames and ignition sources in the immediate area. Use cautious judgment when cleaning up large spills. Clean up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection, gloves and splash goggles. Absorb as much spilled material as possible with rags, sand, vermiculite or other absorbent material. Scrape absorbed material into designated waste containers. Wash area thoroughly with detergent and rinse, taking care to prevent runoff into drains or other waterways. All spilled material, absorbed waste and wash water must be disposed of in accordance with all federal, state and local regulations.
Environmental Precautions	For safety and environmental precaution, please review the entire Safety Data Sheet for necessary information.

Section 7. Handling and Storage

Storage Temperature	Ideal storage temperature is 25°C
Shelf Life	12 Months @ 77°F (25°C)
Storage	Store in a cool, dry place with adequate ventilation. Keep away from flames and high temperatures.
Sensitivity to Static Electricity	No
Sensitivity to Mechanical Impact	No
Special Sensitivity	Avoid excessive heat
Other Precautions	This material should not be spilled, dumped or flushed down water drains, sewers or watercourses.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethy	N/A	N/A	N/A
	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-	N/A	1 ppm, skin, TWA 6 mg/m3, inhalation	N/A
	Terphenyl, hydrogenated	N/A	N/A	N/A
Personal Protective Equipment	Goggles, Gloves, Face Shield, Respirator, CHEMICAL GOGGLES, PROTECTIVE CLOTHING, VENTILATION			
Hazardous Components	Terphenyl, hydrogenated: ACGIH – 0.5 ppm, TWA (non-irradiated)			
Ventilation	Local exhaust ventilation recommended if generating vapor, dust or mist. If exhaust ventilation is not available or inadequate, use NIOSH approved respirator as appropriate.			
Eye protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicated this is necessary to avoid exposure to liquid splashed, mist or dusts.			
Hand protection	Neoprene gloves. Butyl-rubber. Nitrile rubber. Impervious gloves. The breakthrough time of the selected glove(s) must be greater than the intended use period.			
Hygienic Practices - Clothing	Launder contaminated clothes before wearing. Do not smoke or eat where this material is being used. Wash hands before smoking, eating or going to the bathroom			
Skin and Body Protection	Standard issue work clothes. Safety boots - chemical resistant without lace holes.			
Respiratory Protection	Wear appropriate respirator when ventilation is inadequate. During spraying, wear suitable respiratory equipment.			

Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	Amine
Odor Threshold	N/A
Solubility	Slightly soluble
Partition coefficient Water/n-octanol	N/A
VOC%	Negligible
Viscosity	N/A
Specific Gravity	0.96
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>170°C
FP Method	Pensky-Martens Closed Tester
Ph	N/A
Melting Point	N/A
Boiling Point	>176°C
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	N/A
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	<10.34 mmHg @ 21°C
Vapor Density	N/A

Section 10. Stability and Reactivity

Chemical Stability	Stable under recommended storage temperatures and pressures.
Materials to Avoid	Sodium hypochlorite. Organic acids (i.e. acetic acid, citric acid, etc). Mineral acids. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Reactive metals (e.g. sodium, calcium, zinc, etc.). Materials reactive with hydroxyl compounds. Oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition or burning may produce carbon monoxide and/or carbon dioxide, nitrogen oxides and ammonia.
Hazardous Polymerization	Will not occur

Section 11. Toxicological Information

Route of Entry	Eye Contact, Skin Contact, Inhalation, Ingestion
Carcinogen	Carcinogen IARC NTP OSHA Substance Component (group) Specific Regulation COMPONENT There is no evidence that this product poses a carcinogenic risk under normal conditions of handling and use.
Chronic (Long Term) Effects of Exposure	Effects of Chronic Exposure TARGET ORGANS: Eyes; Skin; Kidneys; Liver; Central nervous system RESPIRATORY SENSITIZATION: Sensitizer. May cause allergic reaction. SKIN SENSITIZATION: Sensitizer. May cause allergic reaction.
PRODUCT TOXICOLOGY: Product Information	This health hazard assessment is based on a consideration of the composition of this product. This material caused irritation following skin contact and can cause serious damage to the eyes. COMPONENT: Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine Oral LD50: Mouse 1600 mg/kg Oral LD50: Rabbit 5500 mg/kg Oral LD50: Rat 43400 mg/kg Note: Moderately toxic. Irritant and may cause nausea and vomiting. Corrosive to mouth, throat and stomach. Slightly toxic. Terphenyl, hydrogenated: No hazard in normal industrial use. COMPONENT: Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine Dermal LD50: Rabbit 800 mg/kg Note: Repeated and/or prolong contact may cause skin sensitization. Irritating to the skin. Slightly toxic. Corrosive. Skin sensitizer. Terphenyl, hydrogenated: Irritating to the skin. COMPONENT:

Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine

Note:

Possible respiratory sensitizer. Vapor or aerosol, if generated, can cause irritation of the eyes, nose and respiratory tract.

Possible respiratory sensitizer. Respiratory irritant.

Terphenyl, hydrogenated:

Inhalation LC50 (4hr): Rat > 11.1 mg/l

Note:

Irritating and/or toxic vapor may be released at elevated temperatures.

COMPONENT:

Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine

NOTE ON EYE IRRITATION:

Severe/very severe irritant.

Terphenyl, hydrogenated:

Note: irritating, but does not injure eye tissue.

Section 12. Ecological Information

No ecological testing has been conducted on this product.

Section 13. Disposal

WASTE DISPOSAL
METHOD:

Dispose of in accord with local, state and federal regulations

Empty Container
Precautions

Empty containers must be handled with care due to product residue. Do not heat or cut empty container with electric or gas torch.

Section 14. Transport Information

UN Number

N/A

UN Proper Shipping Name

N/A

DOT Classification

N/A

Packing Group

N/A

All Regulatory Classification

This product is not regulated by CFR, TDG, IMO, IMDG or IATA

DOT

Not hazardous by DOT regulations

Section 15. Regulatory Information

Regulatory Information

TSCA All components are on the TSCA inventory.
Canadian Domestic Substance List (DSL) Is on DSL.
China (IECSC) On the IECSC Inventory.
Japan (ENCS) On the ENCS Inventory.
Australia (AICS) On the AICS Inventory.
Korea (KECI) On the KECI Inventory.
Philippines (PICCS) On the PICCS Inventory.
EINECS All components of this product are listed in EINECS or ELINCS.

SARA - Section 313 (Superfund Amendments and Reauthorization Act of 1986 - 40CFR372) Contains no substances at or above the reporting threshold under Section 313.

CALIFORNIA PROPOSITION 65

WARNING: This product contains the following chemicals that are known to the State of California to cause cancer, birth defects or other reproductive harm. Unless a concentration is specified in Section 2 of the SDS, the below chemicals are present in trace amounts:

COMPONENT: Benzene

CAS NUMBER: 71-43-2

Section 16. Other Information

Revision Date

8/21/2015

HMIS Rating (Not Regulated)

The HMIS Rating for this product is:
Health: 3 Flammability: 1 Reactivity: 0

0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

For Information Purposes Only - No Longer Regulated

Disclaimer

The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication as part of E.V. Roberts' product safety program. It is not intended to constitute performance information concerning the product. No warranty, expressed or implied, or merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. E.V. Roberts does not undertake to furnish advice on such matters.