



Safety Data Sheet

RF 2296 Silicone Part A

Section 1. Identification

| | | | |
|------------------------------|--|----------------------------|----------------|
| Product Identifier | RF 2296 Silicone Part A | | |
| Synonyms | Silicone Rubber Compound | | |
| Manufacturer Stock Numbers | 29707A | | |
| Recommended use | Glass Filled Silicone Polymer | | |
| Uses advised against | Avoid high temperatures. Avoid flames. Incompatible with strong oxidizing agents. Emits toxic fumes under fire conditions. Combustion can produce toxic gases. | | |
| Manufacturer Contact Address | Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA | | |
| | Phone | Emergency Phone | Fax |
| | (310) 204-6159 | (800) 424-9300 CHEMTREC | (310) 202-7247 |
| | Email | Website | |
| | sales@evroberts.com | http://www.evroberts.com | |

Section 2. Hazards Identification

| | |
|----------------|--|
| Classification | ACUTE TOXICITY - ORAL - Category 5 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Single E - Category 3) |
| Signal Word | Warning |
| Pictogram | |

Hazard Statements May be harmful if swallowed
May cause respiratory irritation; or May cause drowsiness or dizziness
Moderately irritating to skin

Precautionary Statements

Response Call a poison center/doctor/ ... /if you feel unwell.
If inhaled: Remove person to fresh air and keep comfortable for breathing.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.
Use only outdoors or in a well-ventilated area.

Storage Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal Refer to manufacturer/Supplier for information on recovery/recycling

Ingredients of unknown 0%
toxicity

Hazards not Otherwise
Classified

EMERGENCY OVERVIEW CAUTION! Irritating to eyes.
Attention: Not for injection into humans.
Form: solid
Color: white
Odor: Slight

Skin contact Mechanical Skin irritation:
Signs/symptoms may include abrasion, redness, pain, and itching.

Ingestion Gastrointestinal irritation:
Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting
and diarrhea.

Inhalation No hazard in normal industrial use.

Medical Conditions None known.

Aggravated by Exposure

Target organ Overexposure causes respiratory disorder, liver and kidney damage.

Chronic Health Hazard This product contains no listed carcinogens according to IARC, ACGIH, NTP
and/or OSHA in concentrations of 0.1 percent or greater. Subchronic exposure
of this material or component in test animals has caused abnormalities in the
following organ(s): Kidney, Liver, Respiratory System

Routes of Entry Skin Contact, Eye Contact

Section 3. Ingredients

| CAS | Ingredient Name | Weight % |
|-------------|---------------------------------------|----------|
| 112926-00-8 | Synthetic Crystalline-free Silica Gel | <3 % |
| 11099-06-2 | Ethyl silicate | 1-5 % |
| 8001-78-3 | Castor oil, hydrogenated | 1-5 % |
| 1314-13-2 | Zinc oxide (ZnO) | 10-30 % |
| 471-34-1 | Limestone | 10-30 % |
| 68951-93-9 | Methylphenylsiloxane Copolymer | 30-60 % |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

| | |
|------------|---|
| Ingestion | Do NOT Induce Vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, if conscience, wash out their mouth with water then give 1 or 2 glasses of water to drink. Refer person to medical personnel for immediate attention. |
| Skin | Wash with soap and water. Get medical attention if irritation develops or persists. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. |
| Eye | Immediately flush eyes with plenty of water for 15 minutes. If irritation persists, continue flushing and obtain medical attention immediately |

Section 5. Fire Fighting Measures

| | |
|--------------------------------|--|
| Suitable Extinguishing Media | <p>FLASH POINT: >100°C; 212°F</p> <p>IGNITION TEMPERATURE: Not applicable</p> <p>FLAMMABLE LIMITS IN AIR - LOWER(%): Not applicable</p> <p>FLAMMABLE LIMITS IN AIR - UPPER(%): Not applicable</p> <p>SENSITIVITY TO MECHANICAL IMPACT: No</p> <p>SENSITIVITY TO STATIC DISCHARGE: Sensitivity to static discharge is not expected.</p> <p>EXTINGUISHING MEDIA: All standard extinguishing agents are suitable.</p> <p>SPECIAL FIRE FIGHTING PROCEDURES: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.</p> |
| Unsuitable Extinguishing Media | N/A |

Section 6. Accidental Release Measures

| | |
|--------------|---|
| Small Spills | Stop leak if without risk. Move containers from spill area. For molten material, allow the product to cool and solidify. Vacuum or sweep up material and place in a designated, labeled appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Wash walking surface with detergent and water to reduce slipping hazard. |
|--------------|---|

Section 7. Handling and Storage

| | |
|----------|-----------------------------------|
| Handling | Avoid contact with skin and eyes. |
|----------|-----------------------------------|

Section 8. Exposure Controls/Personal Protection

| Occupational Exposure Limits | Ingredient Name | ACGIH TLV | OSHA PEL | STEL |
|-------------------------------|--|-----------|----------|------|
| | Synthetic Crystalline-free Silica Gel | N/A | N/A | N/A |
| | Ethyl silicate | N/A | N/A | N/A |
| | Castor oil, hydrogenated | N/A | N/A | N/A |
| | Zinc oxide (ZnO) | N/A | N/A | N/A |
| | Limestone | N/A | N/A | N/A |
| | Methylphenylsiloxane Copolymer | N/A | N/A | N/A |
| Personal Protective Equipment | Goggles, Gloves, Apron, Face Shield, Respirator | | | |
| Respirators | A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. | | | |
| Hand protection | Neoprene gloves. Butyl-rubber. EVAL-Laminate | | | |
| Eye Protection | Chemical safety goggles. Use a full-face shield. | | | |
| Other clothing | Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. | | | |
| Exposure Guidelines | <p>Component : CAS RN : Source : Value</p> <p>Limestone; 471-34-1; ACGIH, TWA; 10 mg/m³ The value is for particulate matter containing no asbestos and < 1% crystalline silica.</p> <p>Zinc oxide; 1314-13-2; OSHA Z1, PEL; Fume 5 mg/m³</p> <p>Zinc oxide; 1314-13-2; OSHA Z1, PEL; Reparable fraction 5 mg/m³</p> <p>Zinc oxide; 1314-13-2; OSHA Z1, PEL; Total dust 15 mg/m³</p> <p>Zinc oxide; 1314-13-2; ACGIH, TWA; Reparable fraction 2 mg/m³</p> <p>Zinc oxide; 1314-13-2; OSHA Z1, STEL; Reparable fraction 10 mg/m³</p> <p>PEL – OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA – Time Weighted Average</p> <p>OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. Sec 29 CFR 1910.1000 (58 RF 35338).</p> | | | |

Section 9. Physical and Chemical Properties

| | |
|---------------------------------------|--------------------|
| Physical State | Paste |
| Color | White |
| Odor | Faint |
| Odor Threshold | N/A |
| Solubility | Insoluble |
| Partition coefficient Water/n-octanol | N/A |
| VOC% | HT |
| Viscosity | N/A |
| Specific Gravity | 1.35 |
| Density lbs/Gal | 1.35 |
| Pounds per Cubic Foot | N/A |
| Flash Point | > 100°C (212°F) |
| FP Method | N/A |
| Ph | N/A |
| Melting Point | N/A |
| Boiling Point | > 168°C (334°F) |
| Boiling Range | N/A |
| LEL | N/A |
| UEL | N/A |
| Evaporation Rate | N/A |
| Flammability | N/A |
| Decomposition Temperature | 150°C (300° F) |
| Auto-ignition Temperature | N/A |
| Vapor Pressure | N/A |
| Vapor Density | N/A |

Section 10. Stability and Reactivity

| | |
|--|--|
| Chemical Stability | Stable under normal conditions. |
| Hazardous Polymerization | Will not occur |
| Hazardous Decomposition or By-Products | Carbon dioxide (CO ₂); Carbon monoxide; Silicon dioxide; May generate formaldehyde at temperatures greater than 150°C (300°F). Sec 10 of MSDS for details. |
| Materials to Avoid | None known. |
| Conditions to Avoid | None listed |

Section 11. Toxicological Information

| | |
|---------------------------------|---|
| Acute Dermal Toxicity | Unknown |
| Acute Oral Toxicity | Unknown |
| Inhalation Toxicity | Unknown |
| Other Toxicological Information | No data available |
| Sensitization | No data available |
| Skin Irritation | No data available |
| Eye Irritation | No data available |
| Mutagenicity | Unknown |
| Carcinogenicity | The National Toxicity Program (NTP) classifies formaldehyde as "known to be a human carcinogen" with respect to nasopharyngeal cancer, sinonasal cancer and myeloid leukemia. The International Agency for Research on Cancer (IARC) classifies formaldehyde as "carcinogenic to humans". U.S. OSHA regulates formaldehyde as a potential human carcinogen. See the OSHA formaldehyde Workplace Standard at 29 CFR 1920.1048 (the "OSHA Standard"). Safe handling and use instructions are provided in this MSDS and in the OSHA Standard. OSHA has identified 0.5 ppm, calculated as an eight-hour time-weighted average ("TWA") concentration, as the "Action Level". Please review and understand the guidance contained in this MSDS, and refer to the OSHA Standard for regulatory requirements that might be applicable to your operation and use. Many studies and other evaluations have been performed concerning formaldehyde's potential to cause cancer. To review some of these studies and for further information go to www.osha.gov ; http://monographs.iarc.fr ; http://ntp-server.niehs.nih.gov ; http://epa.gov ; http://www.nap.edu and other authoritative websites then search on formaldehyde. |

Section 12. Ecological Information

| | |
|---------------------|--------------------|
| Ecotoxicity Effects | No data available. |
| CHEMICAL FATE | No data available. |
| DISTRIBUTION | No data available. |

Section 13. Disposal

| | |
|----------|---|
| Disposal | Dispose of container and unused contents in accordance with federal, state, and local requirements. |
|----------|---|

Section 14. Transport Information

| | |
|-------------------------|---|
| UN Number | N/A |
| UN Proper Shipping Name | N/A |
| DOT Classification | N/A |
| Packing Group | N/A |
| Further Information | Not dangerous goods. The transportation information is not intended to convey all specific regulatory data relating to this material. |

Section 15. Regulatory Information

| | |
|---------------------------|--|
| International Regulations | Chemical Inventories: Canada DSL inventory: All components are listed or exempted Japan inventory of Existing & New Chemical Substances (ENCS): All components are listed or exempted Korea Existing Chemical inventory (KECI): All components are listed or exempted China inventory of Existing Chemical Substances: All components are listed or exempted Australia inventory of Chemical Substances (AICS): All components are listed or exempted Philippines inventory of Chemicals and Chemical Substances (PICCS): All components are listed or exempted. Europe inventory: All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted Canada NDSL inventory: All components are not listed or exempted |
| U.S. Federal Regulations | US REGULATORY INFORMATION CERCLA PRODUCT COMPOSITION Clean Air Act Clean Water Act SARA Section 302 SARA (311,312) Hazard Class: - Acute Health Hazard; Chronic Health Hazard SARA (313) Chemicals |
| Regulatory for Canada | Canadian Regulatory Information WHMIS HAZARD CLASS D-2B: Toxic Materials |
| Other | SCHDLE B/HTSUS : 3910.00.0000 Silicones in primary forms |
| U.S.Prop 65 | ECCN : EAR99 U.S. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) This product does not contain any chemicals known to the State of California to cause cancer, birth defects or any other harm. |

Section 16. Other Information

Revision Date

5/6/2015

HMIS Rating (Not Regulated) The HMIS Rating for this product is:
Health: 1 Flammability: 0 Reactivity: 0

0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

Disclaimer

NOTICE: While the descriptions, designs data, and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. It is provided independently of any sale of the product for purpose of hazard communication as part of E.V. Roberts' product safety program. Many factors may affect processing or application/use. We recommend you make tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties or merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sales. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by E.V. Roberts hereunder are given gratis and E.V. Roberts assumes no obligation or liability for the description, designs, data and information given or results obtained, all such being given and accepted at your risk.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. E.V. Roberts does not undertake to furnish advice on such matters.



Safety Data Sheet

RF 2296 Silicone Part B

Section 1. Identification

| | | | |
|----------------------------|---|----------------------------|----------------|
| Product Identifier | RF 2296 Silicone Part B | | |
| Synonyms | 12-ounce Cartridge of Pre-Blended RTV-577 with Microballoons | | |
| Manufacturer Stock Numbers | 29707B | | |
| Recommended use | Catalyst | | |
| Uses advised against | Can react vigorously with strong oxidizing agents, strong Lewis or mineral acids. Will exotherm when reacting. This reaction accelerates at higher temperatures | | |
| Manufacturer Contact | | | |
| Address | Resin Formulators 18027 Bishop Avenue Carson, CA, 90746 USA | | |
| | Phone | Emergency Phone | Fax |
| | (310) 204-6159 | (800) 424-9300 CHEMTREC | (310) 202-7247 |
| | Email | Website | |
| | sales@evroberts.com | http://www.evroberts.com | |

Section 2. Hazards Identification

| | |
|----------------|---|
| Classification | ACUTE TOXICITY - ORAL - Category 4 EYE DAMAGE/IRRITATION - Category 2B SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Single E - Category 3) |
| Signal Word | Warning |
| Pictogram | The pictogram section contains two red diamond-shaped hazard symbols. The first symbol shows a hand being splashed with liquid from a test tube, representing skin irritation or corrosion. The second symbol is a large black exclamation mark, representing a general warning hazard. |

| | |
|---|--|
| Hazard Statements | Causes eye irritation Harmful if swallowed May cause respiratory irritation Moderately irritating to skin |
| Precautionary Statements | |
| Response | Call a poison center/doctor/ ... /if you feel unwell. If eye irritation persists: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If inhaled: Remove person to fresh air and keep comfortable for breathing. If swallowed: Call a poison center/doctor/ ... / if you feel unwell. Rinse mouth. |
| Prevention | Avoid breathing dust/fume/gas/mist/ vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wash ...thoroughly after handling. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. |
| Disposal | Refer to manufacturer/Supplier for information on recovery/recycling |
| Ingredients of unknown toxicity | 0% |
| Hazards not Otherwise Classified | |
| EMERGENCY OVERVIEW | WARNING! CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE RESPIRATORY TRACT IRRITATION. HEATED MATERIAL CAN CAUSE THERMAL BURNS. |
| Potential Health Effects | |
| Ingestion | Harmful if swallowed. |
| Skin | Causes skin irritation. Harmful if absorbed through the skin. |
| Inhalation | Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. |
| Eye Irritation | Severe eye irritation. |
| Medical Conditions Aggravated by Exposure | Central nervous system disorders. |
| TARGET ORGANS | Central nervous system |
| Chronic Health Hazard | This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Subchronic exposure of this material or component in test animals has caused abnormalities in the following organ(s). Central nervous system. |
| Routes of Entry | Skin Contact, Eye Contact, Inhalation, Ingestion |
| Other Health Effects | None Listed |

Section 3. Ingredients

| CAS | Ingredient Name | Weight % |
|---------|----------------------|----------|
| 77-58-7 | Dibutyltin dilautate | 90 % |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

| | |
|------------|--|
| Ingestion | Do not induce vomiting. Give milk or water. Get immediate medical attention. Careful evacuation of stomach by medical personnel imperative. |
| Skin | Remove contaminated clothing and shoes. Wash skin with soap and water. Get medical attention. Wash contaminated clothing and clean shoes before reuse. |
| Inhalation | Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. |
| Eye | Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention. |

Section 5. Fire Fighting Measures

| | |
|--------------------------------|--|
| Suitable Extinguishing Media | FLASH POINT: >121°C; 249.80°F METHOD: PMCC IGNITION TEMPERATURE: >300 FLAMMABLE LIMITS IN AIR - LOWER(%): 3.3 %(v) FLAMMABLE LIMITS IN AIR - UPPER(%): 19.00 %(v) SENSITIVITY TO MECHANICAL IMPACT: No SENSITIVITY TO STATIC DISCHARGE: Sensitivity to static discharge is not expected. EXTINGUISHING MEDIA: All standard extinguishing media. SPECIAL FIRE FIGHTING PROCEDURES: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing. |
| Unsuitable Extinguishing Media | N/A |

Section 6. Accidental Release Measures

| | |
|---------------------------|---|
| Spills, Leaks or Releases | Clean up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection. Evacuate the area. Prevent further leakage, spillage or entry into drains. Contain and absorb large spillages onto an inert, non-flammable absorbent carrier (such as earth or sand), Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spillage area clean with liquid decontaminant. Notify applicable government authorities if release is reportable. |
|---------------------------|---|

Section 7. Handling and Storage

Handling

Use only in a well-ventilated area. Avoid breathing vapors and/or aerosols. Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. Use personal protective equipment. When using, do not eat, drink or smoke.

Section 8. Exposure Controls/Personal Protection

| Occupational Exposure Limits | Ingredient Name | ACGIH TLV | OSHA PEL | STEL |
|-------------------------------|--|-----------|----------|------|
| | Dibutyltin dilaurate | 0.1 mg | N/A | N/A |
| Personal Protective Equipment | Goggles, Gloves, Face Shield, Respirator | | | |
| Engineering controls | Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. | | | |
| Respiratory Protection | Not ordinarily required | | | |
| Hand protection | Cloth gloves. | | | |
| Eye/Face Protection | Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU). | | | |
| Exposure Guidelines | Component : CAS RN : Source : Value Dibutyltin dilaurate; 77-58-7; ACGIH, TWA; 0.1 mg/m ³ Dibutyltin dilaurate; 77-58-7; ACGIH, STEL; 0.2 mg/m ³ Dibutyltin dilaurate; 77-58-7; ACGIH SKIN_DES; Can be absorbed through the skin. Dibutyltin dilaurate; 77-58-7; OSHA Z1A, TWA; 0.1 mg/m ³ Dibutyltin dilaurate; 77-58-7; OSHA Z1A, SKIN_FINAL; Can be absorbed through the skin. PEL – OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA – Time Weighted Average OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. Sec 29 CFR 1910.1000 (58 RF 35338). | | | |

Section 9. Physical and Chemical Properties

| | |
|---------------------------------------|-----------------------|
| Physical State | Liquid |
| Color | White |
| Odor | Slight smell |
| Odor Threshold | N/A |
| Solubility | Slightly |
| Partition coefficient Water/n-octanol | N/A |
| VOC% | <6 |
| Viscosity | N/A |
| Specific Gravity | 1.28 |
| Density lbs/Gal | -12.8 |
| Pounds per Cubic Foot | N/A |
| Flash Point | > 121°C (249.80°F) |
| FP Method | PMCC |
| Ph | N/A |
| Melting Point | N/A |
| Boiling Point | >300 |
| Boiling Range | N/A |
| LEL | N/A |
| UEL | N/A |
| Evaporation Rate | N/A |
| Flammability | 19.0% |
| Decomposition Temperature | N/A |
| Auto-ignition Temperature | N/A |
| Vapor Pressure | Neg. |
| Vapor Density | N/A |

Section 10. Stability and Reactivity

| | |
|--|--|
| Chemical Stability | Stable under normal conditions. |
| Hazardous Polymerization | Will not occur |
| Hazardous Decomposition or By-Products | Carbon dioxide (CO ₂); formaldehyde; Carbon monoxide; Silicon dioxide; |
| Materials to Avoid | None known. |
| Conditions to Avoid | None listed |

Section 11. Toxicological Information

| | |
|-----------------------|---------|
| Acute Oral Toxicity | Unknown |
| Acute Dermal Toxicity | Unknown |
| Inhalation Toxicity | Unknown |
| Mutagenicity | Unknown |

Section 12. Ecological Information

Ecotoxicity Effects No data available.
CHEMICAL FATE No data available.

Section 13. Disposal

Disposal Dispose of container and unused contents in accordance with federal, state, and local requirements.

Section 14. Transport Information

UN Number 3082
UN Proper Shipping Name LTD QTY - Environmentally hazardous substance, liquid, n.o.s.
(DIBUTYLTINDILAUATE)
DOT Classification 9
Packing Group III
DOT Miscellaneous hazardous material

Section 15. Regulatory Information

U.S. Federal Regulations US REGULATORY INFORMATION

CERCLA PRODUCT COMPOSITION
Clean Air Act
Clean Water Act
SARA Section 302
SARA (311,312) Hazard Class:
- Acute Health Hazard; Chronic Health Hazard
SARA (313) Chemicals

Regulatory for Canada Canadian Regulatory Information
WHMIS HAZARD CLASS
D-2B: Toxic Materials

California Prop. 65 Components This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16. Other Information

Revision Date

5/6/2015

HMIS Rating (Not Regulated) The HMIS Rating for this product is:
Health: 1 Flammability: 0 Reactivity: 0

0=Minimal; 1=Slight; 2=Moderate; 3=Serious; 4=Severe

Disclaimer

NOTICE: While the descriptions, designs data, and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. It is provided independently of any sale of the product for purpose of hazard communication as part of E.V. Roberts' product safety program. Many factors may affect processing or application/use. We recommend you make tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties or merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sales. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by E.V. Roberts hereunder are given gratis and E.V. Roberts assumes no obligation or liability for the description, designs, data and information given or results obtained, all such being given and accepted at your risk.

To determine applicability or effects of any law or regulation with respect to the product, user should consult his legal advisor or the appropriate government agency. E.V. Roberts does not undertake to furnish advice on such matters.